

# Hobie Island Trampoline Kit Instructions

79527001 & 79527011

Included are a pair of trampolines for the Hobie Adventure Island that are designed by Hobie and built in our sail and trampoline loft in Oceanside, CA.

The forward edges of the trampolines have sleeves and the back edges feature snap buckles. The top of each trampoline features a gear pocket and the Port side or left tramp has an added mesh strap that is used for securing the front of the paddle.

To install the tramps begin with the forward AKAs removed from the Island hull. Slide each AKA through the sleeved forward edge of the trampoline and reinstall the crossbar pins. Next locate the Outhaul bungee at the outside forward corner of each trampoline and connect it to the eyelet post on the outside of the forward AKA. Moving back you'll find webbing straps, begin connecting them at the inside near the hull where you'll connect the first inside strap to the crossbar and not the AKA itself. Tighten each strap and go sailing.




Another feature are the forward bungee straps for securing the trampolines while not in use. To use them unbuckle the rear of the trampoline, roll the material up toward the forward AKA and wrap the bungee around an onto the hook.

While sailing snap the two bungees onto themselves to keep them up and out of the water.

Weight capacity for a trampoline is 200 lbs / 90 kg



April 28nd 2009



[hobiekayaks.com](http://hobiekayaks.com)



# Hobie Island Trampoline Kit Instructions

79527001 & 79527011

Included are a pair of trampolines for the Hobie Adventure Island that are designed by Hobie and built in our sail and trampoline loft in Oceanside, CA.

The forward edges of the trampolines have sleeves and the back edges feature snap buckles. The top of each trampoline features a gear pocket and the Port side or left tramp has an added mesh strap that is used for securing the front of the paddle.

To install the tramps begin with the forward AKAs removed from the Island hull. Slide each AKA through the sleeved forward edge of the trampoline and reinstall the crossbar pins. Next locate the Outhaul bungee at the outside forward corner of each trampoline and connect it to the eyelet post on the outside of the forward AKA. Moving back you'll find webbing straps, begin connecting them at the inside near the hull where you'll connect the first inside strap to the crossbar and not the AKA itself. Tighten each strap and go sailing.



Another feature are the forward bungee straps for securing the trampolines while not in use. To use them unbuckle the rear of the trampoline, roll the material up toward the forward AKA and wrap the bungee around an onto the hook.

While sailing snap the two bungees onto themselves to keep them up and out of the water.

Weight capacity for a trampoline is 200 lbs / 90 kg



April 28nd 2009



[hobiekayaks.com](http://hobiekayaks.com)

