

Tandem Island Trampoline Kit Instructions.

88527001 & 88527011

Included are a pair of trampolines for the Hobie Tandem Island that are designed by Hobie and built in our sail & trampoline loft in Oceanside, CA.

The forward edges of the trampolines have sleeves and the back edges feature snap buckles. The top of each trampoline features a gear pocket and both sides feature an added mesh strap that is used for securing the front of each paddle.

To install the tramps begin with the forward AKAs removed from the Island hull. Slide each AKA through the sleeved forward edge of the trampoline and reinstall the crossbars. Next locate the Outhaul bungee at the outside forward corner of each trampoline and connect it to the eyelet post on the outside of the forward AKA. Moving back you'll find webbing straps, begin connecting them at the inside near the hull where you'll connect the first inside strap to the crossbar and not the AKA itself. Tighten each strap and go sailing.

Another feature are the forward bungee straps for securing the trampolines while not in use. To use them unbuckle the rear of the trampoline, roll the material up toward the forward AKA and wrap the bungee around and onto the hook.

While sailing snap the two bungees onto themselves to keep them up and out of the water.

Weight capacity for a trampoline is 200 lbs / 90 kg



February 3rd 2010



hobiekayaks.com



Tandem Island Trampoline Kit Instructions.

88527001 & 88527011

Included are a pair of trampolines for the Hobie Tandem Island that are designed by Hobie and built in our sail & trampoline loft in Oceanside, CA.

The forward edges of the trampolines have sleeves and the back edges feature snap buckles. The top of each trampoline features a gear pocket and both sides feature an added mesh strap that is used for securing the front of each paddle.

To install the tramps begin with the forward AKAs removed from the Island hull. Slide each AKA through the sleeved forward edge of the trampoline and reinstall the crossbars. Next locate the Outhaul bungee at the outside forward corner of each trampoline and connect it to the eyelet post on the outside of the forward AKA. Moving back you'll find webbing straps, begin connecting them at the inside near the hull where you'll connect the first inside strap to the crossbar and not the AKA itself. Tighten each strap and go sailing.

Another feature are the forward bungee straps for securing the trampolines while not in use. To use them unbuckle the rear of the trampoline, roll the material up toward the forward AKA and wrap the bungee around and onto the hook.

While sailing snap the two bungees onto themselves to keep them up and out of the water.

Weight capacity for a trampoline is 200 lbs / 90 kg



February 3rd 2010



hobiekayaks.com

