

## FRONT HATCH SEAL, PA12/14/17T

Part #: 71707004

### Tools Needed:

Rubbing alcohol

Shop Rag

Super Glue



### Step 1:

The TrimLok seal is pre-cut to fit the underside of the front cargo hatch on the Pro Angler 14. If you are installing the TrimLok upgrade on a Pro Angler 12 or Pro Angler 17t, trim to the following specs:

<b>Kayak Model</b>	<b>Linear Feet</b>
Pro Angler 12	5.08'
Pro Angler 17T	5.42'

### Step 2:

Thoroughly clean the under-side of the Pro Angler front cargo hatch with rubbing alcohol and a clean shop rag.

### Step 3:

Once the rubbing alcohol has completely evaporated and the surface is dry, start the installation by peeling approx. 6" of the adhesive backing off and adhering the TrimLok to the perimeter of the underside of the hatch lid (as shown in the photo above). Starting and terminating the seal at the aft end of the hatch is recommended. Repeat the peel-and-stick process until TrimLok lines the entire perimeter of the hatch lid. The TrimLok seal is pliable enough to turn corners with, so you DO NOT need to cut to accommodate corners.

### Step 4:

For an extra secure seal, use super glue to close the seam created where each end of the TrimLok meets. Using a piece of plastic or a putty knife to spread the glue between the seam is an effective method for applying an even coat of glue.